

Q8 Formula Excel 5W-40

Synthetic ACEA A3/B4 passenger car engine oil

Description

Q8 Formula Excel 5W-40 is a synthetic allround high SAPS engine oil for passenger cars and light duty commercial vehicles. This product guarantees advanced engine protection and facilitates easy starting at low temperatures. It is designed to counter sludge formation and minimizes oil consumption. It meets the requirements of ACEA A3/B4.

Applications

Q8 Formula Excel 5W-40 is developed for passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or diesel engines and direct injection diesel engines. It is especially recommended for high performance, multi-valve engines with a catalyst. It meets the requirements of ACEA A3/B4.

Benefits

- Outstanding oil film strength under all engine operating conditions.
- Outstanding engine protection after cold starting.
- Excellent protection against rust and corrosion.
- Outstanding friction reduction.

Specifications & Approvals

ACEA	A3/B4	PSA	B71 2300
API	CF	Porsche	A40
API	SN	Renault	RN 0700
BMW	Longlife-01	Renault	RN 0710
Ford	M2C 917-A	VAG	VW 502.00
GM	LL-B-025	VAG	VW 505.00
JASO	MA2	VAG	VW 505.01
MB	229.3	Volvo	VCC 95200356

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.850
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.9
Kinematic Viscosity, 40 °C (extrapolated)	D 445	mm ² /s	81.9
Viscosity Index	D 2270	-	176
Apparent Viscosity, -30 °C	D 5293	mPa.s	6400
Flash Point, P-M	D 93	°C	221
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.