

Q8 Axle Oil GL-5 75W-90

Synthetic based API GL-5 transmission fluid

Description

Q8 Axle Oil GL-5 75W-90 is a premium performance transmission fluid, developed for heavy duty vehicles and passenger cars. It can be used for final drives, differentials, rear axles and transfer boxes meeting the API GL-5 specification.

Applications

Q8 Axle Oil GL-5 75W-90 is developed for heavy duty vehicles and passenger cars. It can be used for final drives, differentials, rear axles and transfer boxes, meeting the API GL-5 specification.

Benefits

- Outstanding axle wear protection.
- Superb gear protection under heavy duty conditions.
- Outstanding protection against rust and corrosion.
- Improved shear stability for a stable viscosity during use

Specifications & Approvals

API	GL-5	ZF	TE-ML 16B
MIL	L-2105D	ZF	TE-ML 17B
ZF	TE-ML 05A	ZF	TE-ML 19B

Properties

	Method	Unit	Typical	
Density, 15 °C	D 4052	g/ml	0,87	
Kinematic Viscosity, 40 °C	D 445	mm²/s	101.1	
Kinematic Viscosity, 100 °C	D 445	mm²/s	14.8	
Viscosity Index	D 2270	-	152	
Brookfield Viscosity, -40 °C	D 2983	Pa.s	108.1	
Flash Point, COC	D 92	°C	168	

The figures above are not a specification. They are typical figures obtained within production tolerances.